

SPF 6000/12000T DVM-MPV

- Low frequency inverter 120/240Vac Split Phase output
- Integrated MPPT charge controller
- Optional WIFI/ GPRS remote monitoring
- Built-in pure copper low frequency transformer
- Configurable grid or solar input priority



GROWATT

P O W E R

- I N G

T O M O -

R R O W

Datasheet	SPF 6000T DVM-MPV	SPF 12000T DVM-MPV
Battery Voltage	48VDC	
Battery Type	Lithium /Lead-acid	
INVERTER OUTPUT		
Rated Power	6KW	12KW
Surge Rating	18KW	36KW
Waveform	Pure sine wave/ same as input (bypass mode)	
Nominal Output Voltage RMS	104-110-115-120/208-220-230-240VAC(optional)	
Output Frequency	50Hz /60Hz +/-0.5 Hz	
Inverter Efficiency(Peak)	88%	
Transfer Time	10ms	
SOLAR CHARGER		
Maximum PV Charge Current	80A	120A
Maximum PV Array Power	5000W	7000W
Number of independent MPP trackers/ strings per MPP tracker	1/1	2/1
MPPT Range @ Operating Voltage(VDC)	60-245VDC	
Maximum PV Array Open Circuit Voltage	250V	
Maximum Efficiency	97%	
AC INPUT		
Voltage	240VAC	
Selectable Voltage Range	184-272VAC(UPS);154-272VAC(APL)	
Frequency Range	50Hz/60Hz (Auto sensing)	
Max. Charging Current	60A	100A
MECHANICAL SPECIFICATIONS		
Protection Degree	IP20	
Dimensions (W/H/D)	360/540/218mm	380/650/225mm
Weight	52kg	75kg
OPERATING ENVIRONMENT		
Operation Temperature Range	0° C to 50° C	
Altitude	<2000W	